


Thermal Management

WHY USE A STAMPED CPU HEATSINK?

ASSMANN

WSW components

STAMPED CPU HEATSINKS



Thermal Management

WHY USE A STAMPED CPU HEATSINK?


ASSMANN

WSW components

STAMPED CPU HEATSINKS

PROMISE AN
IMPROVED HEAT
DISSIPATION IN A PASSIVE
TO BE COOLED CPU AREA

BUT HOW ?



BUT HOW ?


CROSS CUT heatsink

Cross Cut heatsink absorb heat from a chip

⇒ Conduction

and releases it to the ambient air

⇒ Convection




BUT HOW ?

CROSS CUT heatsink

Hot spots

- ⇒ Heat accumulation is caused by high thermal radiation and low convection
- ⇒ Reason: Mutual heating of the cooling fins (square geometry)
- ⇒ Result: Formation of a hotspot. Convection and heat radiation is only optimal in the outer area.




BUT HOW ?

STAMPED CPU heatsink

Optimized geometry of heatsink

⇒ improved convection, because of stack-effect (holes in the base plate)

⇒ Improved heat radiation
(no heat accumulation of the cooling fins)



Mounting options/methods e.g.

Push Pin


Example:

Existing or additional holes in
side plate can be 30x30mm
this distance 50mm
⇒ base size 900mm²



Additional advantage:

Side plate can be stamped with the same
12x42mm hole spacing
⇒ same hole distance 50mm
⇒ base size 764mm²
⇒ difference 864mm²




Thermal Management

WHY USE A STAMPED CPU HEATSINK?

ASSMANN

WSW components



Application example

Due to optimized performance and space usage, two different


Cross-Cut CPU heat sink (1 + 2) can be replaced by a stamped heat sink

cross cut 1

Thermal Management

WHY USE A STAMPED CPU HEATSINK?

ASSMANN
WSW components



Application example

Due to optimized performance and space usage, two different

Cross-Cut CPU heat sink (1 + 2) can be replaced by a stamped heat sink


cross cut 2

Thermal Management

WHY USE A STAMPED CPU HEATSINK?

ASSMANN

WSW components



Application example

Due to optimized performance and space usage, two different

Cross-Cut CPU heat sink (1 + 2) can be replaced by a stamped heat sink


cross cut 1

cross cut 2

Mounting options/methods


Push pin

Existing or additional holes in the base plate can be used for this purpose.




Solder Pin

Solder pins can additionally be pressed in the base plate, to solder on PCB



Thermal Adhesive Tape

Thermal adhesive tape can be pre-applied to the heatsink for mounting onto the chip



Thermal adhesive


Can be ordered separately to glue the heatsink



Modifications

Cut-outs in the heat sink can be customer-tailored to the application by modifying the tooling.

This allows adjacent components to be bypassed without reducing the base plate of the heat sink.



Thermal Management

WHY USE A STAMPED CPU HEATSINK?

ASSMANN
WSW components

Material

Aluminium Alloy AL1050 in different material thickness

Customer tailored


Modifications of all dimensions and special perforations are possible.

Samples can be handmade without tooling charges.

Special surface treatment

Packing acc. customers request





CPU heatsinks

V2138N1

CPU heatsinks

Stamped version

dimensions 16x65x65mm

nature anodized

material AL1050

Picture: hand made sample

Part number: V2138N1

product group: CPU heatsinks

style: Stamped version

height in mm: 16,00

width in mm: 65,00

length in mm: 65,00

surface: nature anodized






material: AL1050


version: stamped

Thermal Management

WEBSITE PRODUCT DETAILS

ASSMANN
WSW components

	1	2	3	4	5	6	7																																																																										
A								A																																																																									
B								B																																																																									
C								C																																																																									
D								D																																																																									
E	 <p>Note: ① Material: AL 1050 Finish: Nature anodized</p>							E																																																																									
F								F																																																																									
G	<div><div><div>RoHS compliant</div><div>Unit: mm</div></div><table><tr><td>Scale</td><td>Free</td><td></td><td></td><td></td><td></td><td>Date</td><td>Name</td><td colspan="2">Customer-No.</td></tr><tr><td colspan="2">TOLERANCE</td><td></td><td></td><td></td><td></td><td>Drawn</td><td>02.05.2013</td><td>Amy</td><td rowspan="4">ASSMANN WSW-No. V2138N1</td></tr><tr><td>Less 10</td><td>±0,15</td><td></td><td></td><td></td><td></td><td>Approved</td><td>11.07.2014</td><td>Amy</td></tr><tr><td>10~30</td><td>±0,20</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>31~50</td><td>±0,25</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>51~100</td><td>±0,30</td><td>①</td><td>Change the material</td><td>11.07.2014</td><td>Amy</td><td colspan="3" rowspan="3"></td><td>Drawing-No.</td><td rowspan="2">ASS 2106 HS</td><td rowspan="2">rev01</td></tr><tr><td>DIM</td><td>Tol</td><td>②</td><td>Drawn</td><td>02.05.2013</td><td>Amy</td></tr><tr><td>Angle</td><td>±1°</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td><td>Replace</td><td>Sheet</td></tr></table></div>							Scale	Free					Date	Name	Customer-No.		TOLERANCE						Drawn	02.05.2013	Amy	ASSMANN WSW-No. V2138N1	Less 10	±0,15					Approved	11.07.2014	Amy	10~30	±0,20								31~50	±0,25								51~100	±0,30	①	Change the material	11.07.2014	Amy				Drawing-No.	ASS 2106 HS	rev01	DIM	Tol	②	Drawn	02.05.2013	Amy	Angle	±1°	Id.	Modification	Date	Name	Replace	Sheet	G
Scale	Free					Date	Name	Customer-No.																																																																									
TOLERANCE						Drawn	02.05.2013	Amy	ASSMANN WSW-No. V2138N1																																																																								
Less 10	±0,15					Approved	11.07.2014	Amy																																																																									
10~30	±0,20																																																																																
31~50	±0,25																																																																																
51~100	±0,30	①	Change the material	11.07.2014	Amy				Drawing-No.	ASS 2106 HS	rev01																																																																						
DIM	Tol	②	Drawn	02.05.2013	Amy																																																																												
Angle	±1°	Id.	Modification	Date	Name				Replace	Sheet																																																																							
H								H																																																																									
	1	2	3	4	5	6	7	KT17																																																																									



CPU heatsinks

V2139N1

CPU heatsinks

Stamped version

dimensions 16x65x53mm

nature anodized

material AL1050

Picture: hand made sample

Part number: V2139N1

product group: CPU heatsinks

style: Stamped version

height in mm: 16,00

width in mm: 65,00

length in mm: 53,00

surface: nature anodized


material: AL1050

version: stamped

Thermal Management

WEBSITE PRODUCT DETAILS

ASSMANN
WSW components





CPU heatsinks

V2140N1

CPU heatsinks

Stamped version

dimensions 14x55x50mm

nature anodized

material AL1050





Picture: hand made sample

Part number:	V2140N1
product group:	CPU heatsinks
style:	Stamped version
height in mm:	14,00
width in mm:	55,00
length in mm:	50,00
surface:	nature anodized
material:	AL1050
version:	stamped

Thermal Management

WEBSITE PRODUCT DETAILS

ASSMANN
WSW components

	1	2	3	4	5	6	7																																																																								
A	<div><p>Note: ① Material: AL 1050 Finish: Nature anodized</p><p>Pin material: Fe Plating: Tin</p><p>Detail A 2 : 1</p></div>							A																																																																							
B								B																																																																							
C								C																																																																							
D								D																																																																							
E								E																																																																							
F	<div><p>RoHS compliant Unit: mm</p><table><tr><td>Scale</td><td>Free</td><td></td><td></td><td></td><td></td><td>Date</td><td>Name</td><td>Customer-No.</td></tr><tr><td colspan="2">TOLERANCE</td><td></td><td></td><td></td><td></td><td>Drawn</td><td>02.05.2013</td><td>Amy</td></tr><tr><td>Less 10</td><td>±0.15</td><td></td><td></td><td></td><td></td><td>Approved</td><td>11.07.2014</td><td>Amy</td></tr><tr><td>10~30</td><td>±0.20</td><td></td><td></td><td></td><td></td><td></td><td></td><td>ASSMANN WSW-No. V2140N1</td></tr><tr><td>31~50</td><td>±0.25</td><td></td><td></td><td></td><td></td><td></td><td></td><td>Drawing-No.</td></tr><tr><td>51~100</td><td>±0.30</td><td>①</td><td>Change the material</td><td>11.07.2014</td><td>Amy</td><td colspan="2" rowspan="2"></td><td>ASS 2108 HS rev01</td></tr><tr><td>DIM</td><td>Tol</td><td>②</td><td>Drawn</td><td>02.05.2013</td><td>Amy</td><td>Replace</td><td>Sheet</td></tr><tr><td>Angle</td><td>±1°</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td><td></td><td></td><td></td></tr></table></div>							Scale	Free					Date	Name	Customer-No.	TOLERANCE						Drawn	02.05.2013	Amy	Less 10	±0.15					Approved	11.07.2014	Amy	10~30	±0.20							ASSMANN WSW-No. V2140N1	31~50	±0.25							Drawing-No.	51~100	±0.30	①	Change the material	11.07.2014	Amy			ASS 2108 HS rev01	DIM	Tol	②	Drawn	02.05.2013	Amy	Replace	Sheet	Angle	±1°	Id.	Modification	Date	Name				F
Scale								Free					Date	Name	Customer-No.																																																																
TOLERANCE												Drawn	02.05.2013	Amy																																																																	
Less 10								±0.15					Approved	11.07.2014	Amy																																																																
10~30								±0.20							ASSMANN WSW-No. V2140N1																																																																
31~50	±0.25							Drawing-No.																																																																							
51~100	±0.30	①	Change the material	11.07.2014	Amy			ASS 2108 HS rev01																																																																							
DIM	Tol	②	Drawn	02.05.2013	Amy			Replace	Sheet																																																																						
Angle	±1°	Id.	Modification	Date	Name																																																																										
G	G																																																																														
H								H																																																																							
	1	2	3	4	5	6	7	KT17																																																																							