

| | | | | | | | | |
|---|--|---|---|---|---|---|---|--------|
| | 1 | 2 | 3 | 4 | 5 | 6 | 7 | |
| A | <div data-bbox="369 151 1960 1077"> <p>Technical drawing of ASSMANN ASS 2107 HS component. The drawing includes a top view, a side view, and a detail view of a corner. Dimensions are provided in mm.</p> <p>Top View Dimensions:</p> <ul style="list-style-type: none"> Overall width: 53±0,30 Overall height: 64±0,30 Inner width: 47 Inner height: 35±0,20 Distance from top edge to first hole row: 14,5 Distance from bottom edge to first hole row: 14,5 Distance from left edge to first hole column: 14,5 Distance from right edge to first hole column: 14,5 Hole diameter: $\phi 1,2$ Top hole spacing: 6x12,86 Right hole spacing: 6x11,6 Bottom hole spacing: 11x3,2 Left hole spacing: 9,15 Distance from top edge to last hole row: 3,75 Distance from bottom edge to last hole row: 3,75 Distance from left edge to last hole column: 3,75 Distance from right edge to last hole column: 3,75 Distance from top edge to first hole row: 35±0,20 Distance from bottom edge to first hole row: 35±0,20 Distance from left edge to first hole column: 35±0,20 Distance from right edge to first hole column: 35±0,20 Distance from top edge to last hole row: 49,5±0,20 Distance from bottom edge to last hole row: 49,5±0,20 Distance from left edge to last hole column: 49,5±0,20 Distance from right edge to last hole column: 49,5±0,20 <p>Side View Dimensions:</p> <ul style="list-style-type: none"> Overall height: 16±0,25 <p>Detail View Dimensions:</p> <ul style="list-style-type: none"> Depth: 0,1mm </div> | | | | | | | A |
| B | | | | | | | | B |
| C | | | | | | | | C |
| D | | | | | | | | D |
| E | | | | | | | | E |
| F | | | | | | | | F |
| G | <div data-bbox="168 1125 504 1189"> <p>RoHS compliant Unit: mm</p> </div> <div data-bbox="1579 885 1892 989"> <p>Note: ① Material: AL 1050 Finish: Nature anodized</p> </div> | | | | | | | G |
| H | | | | | | | | H |
| | 1 | 2 | 3 | 4 | 5 | 6 | 7 | KT1752 |