


## SOLVING THERMAL MANAGEMENT CHALLENGES IN A MINIMUM SPACE

WHITE PAPER

VERSION 1.0



PGS




FLEXIBLE



FOLDABLE



SLICEABLE



THERMAL  
CONDUCTIVITY

**ELECTRONIC EQUIPMENT NEEDS AN EFFICIENT MEANS OF MANAGING AND DISPERSING HEAT AS SYSTEMS CONTINUE TO SHRINK IN SIZE.**

## INDEX

---

Introduction . . . . .	3
What is PGS? . . . . .	3
Features. . . . .	4
Usage and results. . . . .	5
Efficacy of PGS. . . . .	6
Applications . . . . .	7
Alternative solutions . . . . .	8
Product overview . . . . .	8

## SOLVING THERMAL MANAGEMENT CHALLENGES IN A MINIMUM SPACE

**ELECTRONIC EQUIPMENT NEEDS AN EFFICIENT MEANS OF MANAGING AND DISPERSING HEAT AS SYSTEMS CONTINUE TO SHRINK IN SIZE.**

### INTRODUCTION


Heat is a killer for electronic systems. As applications get thinner and lighter, this statement has never been more true, yet space and weight restrictions – especially in portable mobile devices – mean that conventional solutions may not be feasible. But it's not just consumer products such as smartphones, tablets and cameras that are at risk. Communications infrastructure equipment cram more and more complex electronics systems into a small space; electric (Eco) and hybrid cars require long-lasting, lightweight batteries; the advent of the smart factory (Industry 4.0) calls for greater levels of monitoring and control; solar panels (ironically) need to be able to cope with constant exposure to the sun; modern medical devices must be able to be worn comfortably.

All these examples require heat to be transferred or dispersed effectively, using a minimum amount of space. Pyrolytic Graphite Sheet (PGS) is a new, ultra-light graphite interface film material, developed by Panasonic, which has a thermal conductivity up to five times greater than copper. It is pliable enough to be cut and folded into complex three dimensional shapes then simply stuck onto the heat source to diffuse the heat or provide a path for heat to flow to a cold wall.

### WHAT IS PGS?

Pyrolytic Highly Oriented Graphite Sheet is made of graphite with a structure that is close to a single crystal. It is produced from polymeric film using a heat de-composition process. The hexagonal crystal structure of graphite is arranged uniformly in a horizontal 2D structure see figure 1.

FIGURE 1– WHAT IS PGS?



## SOLVING THERMAL MANAGEMENT CHALLENGES IN A MINIMUM SPACE


**ELECTRONIC EQUIPMENT NEEDS AN EFFICIENT MEANS OF MANAGING AND DISPERSING HEAT AS SYSTEMS CONTINUE TO SHRINK IN SIZE.**

### FEATURES


PGS has a number of features which make it highly suitable as an easy-to-use, space-saving, thermal management solution:

- it is very thin – available in a range of thicknesses from 100µm down to 10µm – and has excellent thermal conductivity from 700 to 1,950W/m.K which is two to five times higher than copper and up to seven times better than aluminium (see fig 2)
- it is flexible and pliable so it can be easily cut and folded into a complex shape. With a bend radius of 2mm, sheets can be bent through 180 degrees more than 3,000 times, and its thermal conductivity is unaffected if sharp folds are avoided; the material is very stable so it is resistant to environmental effects and shows no deterioration with age
- PGS can provide some shielding to electromagnetic noise, providing a simultaneous EMI and thermal solution (see fig 3).

**FIGURE 2 – COMPARISON OF THERMAL CONDUCTIVITY (A-B PLANE)**



**FIGURE 3 – A-B PLANE (KEC METHOD)**




## SOLVING THERMAL MANAGEMENT CHALLENGES IN A MINIMUM SPACE

**ELECTRONIC EQUIPMENT NEEDS AN EFFICIENT MEANS OF MANAGING AND DISPERSING HEAT AS SYSTEMS CONTINUE TO SHRINK IN SIZE.**

### USAGE AND RESULTS


PGS film is used to transfer heat away from a heat source, or to diffuse or spread heat away from a hot spot (A>B) as shown in figure 4.

**FIGURE 4 – THERMAL TRANSFER**



It can also be used as a highly-efficient thermal interface material as in figure 5.

**FIGURE 5 – THERMAL INTERFACE**



## SOLVING THERMAL MANAGEMENT CHALLENGES IN A MINIMUM SPACE







**ELECTRONIC EQUIPMENT NEEDS AN EFFICIENT MEANS OF MANAGING AND DISPERSING HEAT AS SYSTEMS CONTINUE TO SHRINK IN SIZE.**

### EFFICACY OF PGS

The efficacy of PGS in reducing IC hot spot temperatures is demonstrated in figure. The temperatures at the ABS (Acrylnitril-Butadien-Styrol) surface, the IC and the PCB are shown for two different 70 μm thick PGS sheet sizes.

FIGURE 6 – APPLICATION EXAMPLE OF PGS

◆Heat distribution of the ABS surface with PGS70μ: Diffused the heat and broke the heat spot.

Model	Type A	Type A-1	Type A-2	Type B	Type B-1	Type B-2
						
PGS size (mm)	without	25×40×0.07 (Large)	25×25×0.07 (Small)	without	25×40×0.07 (Large)	25×25×0.07 (Small)
Silicon	with	with	with	without	without	without
Result						
Temp. (°C)						
Surface	99.85	83.84	89.08	93.65	77.17	80.86
IC	101.9	88.89 (-13.0)	93.26 (-8.6)	103.2	99.76	100.96
PWB	96.25	85.31	89.06	97.26	94.19	95.31

## SOLVING THERMAL MANAGEMENT CHALLENGES IN A MINIMUM SPACE

**ELECTRONIC EQUIPMENT NEEDS AN EFFICIENT MEANS OF MANAGING AND DISPERSING HEAT AS SYSTEMS CONTINUE TO SHRINK IN SIZE.**

### APPLICATIONS

Two examples show how PGS film can be used.

Figure 7 demonstrates how heat can be transferred away from an IC (LED) to the casing in a camera design, reducing the heat sinking that is required.

FIGURE 7 – THERMAL TRANSFER





Figure 8 shows how when applied in a IGBT or switching FET module, PGS acts as a thermal interface, reducing the thermal contact resistance and thermal soaking required.

FIGURE 8 – REDUCTION OF THERMAL RESISTANCE AND SOAKING



## SOLVING THERMAL MANAGEMENT CHALLENGES IN A MINIMUM SPACE

ELECTRONIC EQUIPMENT NEEDS AN EFFICIENT MEANS OF MANAGING AND DISPERSING HEAT AS SYSTEMS CONTINUE TO SHRINK IN SIZE.







### ALTERNATIVE SOLUTIONS

PGS has a lower thermal resistance than silicon sheet material and graphite products from other manufacturers. Silicone grease has a lower thermal resistance, but it has the disadvantage of drying up over time and losing effectiveness. Also it is less easy to apply uniformly so results can be variable.

### PRODUCT OVERVIEW

PGS is available as sheet only, or in combination with a number of standard and high heat resistance adhesive options. Additionally, for higher isolation requirements PET tape is available.




### Standard PGS Types

Type	PGS only	Adhesive Types		Laminated Types (Insulation + Adhesive)		
	S Type	A-A Type	A-M Type	A-PA Type	A-PM Type	A-DM Type
Front Face	–	–	–	Polyester Tape Standard Type 30µm	Polyester Tape Standard Type 30µm	Polyester Tape Thin Type 10µm
Rear Face	–	Insulative adhesion type: 30µm	Insulative thin adhesion type: 10µm	Insulative adhesion type: 30 µm	Insulative thin adhesion type: 10 µm	Insulative thin adhesion type: 10 µm
Structure						
Features	<ul style="list-style-type: none"> <li>&gt; High thermal conductivity</li> <li>&gt; High flexibility</li> <li>&gt; Low thermal resistance</li> <li>&gt; Available up to 400°C</li> <li>&gt; Conductive Material</li> </ul>	<ul style="list-style-type: none"> <li>&gt; With insulation material on one side</li> <li>&gt; With strong adhesive tape for putting chassis</li> <li>&gt; Withstanding voltage: 2kV</li> </ul>	<ul style="list-style-type: none"> <li>&gt; With insulation material on one side</li> <li>&gt; Low thermal resistance comparison with A-A type</li> <li>&gt; Withstanding voltage: 1kV</li> </ul>	<ul style="list-style-type: none"> <li>&gt; With insulation material on both sides</li> <li>&gt; Withstanding voltage: PET tape: 4kV adhesive tape: 2kV</li> </ul>	<ul style="list-style-type: none"> <li>&gt; With insulation material on both sides</li> <li>&gt; Withstanding Voltage: PET tape: 4kV adhesive tape: 1kV</li> </ul>	<ul style="list-style-type: none"> <li>&gt; With insulation material on both sides</li> <li>&gt; Withstanding Voltage: PET tape: 1kV adhesive tape: 1kV</li> </ul>
Withstand temperature	400°C	100°C	100°C	100°C	100°C	100°C
Standard Size	115x180mm	90x115mm	90x115mm	90x115mm	90x115mm	90x115mm
Maximum Size	180x230mm 150x180mm (25µm)	115x180mm	115x180mm	115x180mm	115x180mm	115x180mm

## SOLVING THERMAL MANAGEMENT CHALLENGES IN A MINIMUM SPACE

**ELECTRONIC EQUIPMENT NEEDS AN EFFICIENT MEANS OF MANAGING AND DISPERSING HEAT AS SYSTEMS CONTINUE TO SHRINK IN SIZE.**

### High Heat Resistance PGS Types

Type	A-V Type	A-RV Type	A-KV Type
Front Face	–	High heat resistance and insulation type: 13µm	High heat resistance and insulation type: 30µm
Rear Face	High heat resistance and insulation adhesive type: 18µm	High heat resistance and insulation adhesive type: 18µm	High heat resistance and insulation adhesive type: 18µm
Structure			
Features	<ul style="list-style-type: none"> <li>&gt; With high heat resistance and insulation tape on one side</li> <li>&gt; Withstanding voltage adhesive tape: 2kV</li> </ul>	<ul style="list-style-type: none"> <li>&gt; With high heat resistance and insulation tape on both sides</li> <li>&gt; Withstanding voltage PEEK tape: 2kV</li> <li>&gt; Withstanding voltage adhesive tape: 2kV</li> </ul>	<ul style="list-style-type: none"> <li>&gt; With high heat resistance and more insulated tape on both sides</li> <li>&gt; Withstanding Voltage Pt tape: 5kV</li> <li>&gt; Withstanding voltage adhesive tape: 2kV</li> </ul>
Withstand temperature	150°C	150°C	150°C (Polyimide: 180°C)
Standard Size	90x115mm	90x115mm	90x115mm
Maximum Size	115x180mm	115x180mm	115x180mm

